



## Fitting Instructions for

### Honda CB500X/F Rear Rack RRP 445

*NOTE : BEFORE COMMENCING WORK ON THE CONVERSION, TAKE TIME TO READ THE INSTRUCTIONS CAREFULLY. ALL WORK CAN BE CARRIED OUT BY A COMPETENT MECHANIC, BUT IF YOU ARE UNSURE PLEASE CONTACT US OR A MECHANICAL PROFESSIONAL.*

*KEEP ALL PARTS THAT ARE REMOVED, AS IT IS POSSIBLE TO REMOVE OUR KITS AND RETURN THE BIKE TO STANDARD, IF REQUIRED*

**Note: The Rear Rack will not fit without our Solo Rear Rack Mount Kit RRP 444, or Soft Luggage Racks RRP 440, fitted first.**

1. Remove seat.	
2. Place Rear Rack on top of Solo Rack Mount RRP 444, so that all 4 holes align.	
3. Insert each M8x25 CSK screw, and CSK washer, into each of the 4 holes, from the top.	
4. Tighten, using an M8 nyloc nut, and washer, supplied on the underside of each screw. Do not fully tighten.	
5. Check alignment of rack to rear of bike, and check rubber buffer on underside is held securely in the hole in the rack.	
6. Once alignment is satisfactory, then tighten fully all remaining screws.	
7. Replace seat.	